

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse COOL-COLOR, silk matt HB 65285-9005

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)
Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

2. Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)
Skin Sens. 1A H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms ***



Signal word ***

Warning

Hazard statements ***

H317 May cause an allergic skin reaction.

Precautionary statements ***

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

P362+P364 Take off contaminated clothing and wash it before reuse.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains *** 2-methyl-2H-isothiazol-3-one; 1,2-benzisothiazol-3(2H)-one

3. Composition/information on ingredients *****Hazardous ingredients *******1,2-benzisothiazol-3(2H)-one**

CAS No.	2634-33-5			
EINECS no.	220-120-9			
Concentration		<	0,05	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 4		H302	
	Skin Irrit. 2		H315	
	Eye Dam. 1		H318	
	Skin Sens. 1		H317	
	Aquatic Acute 1		H400	
	Aquatic Chronic 2		H411	

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 >= 0,05 %

2-methyl-2H-isothiazol-3-one

CAS No.	2682-20-4			
EINECS no.	220-239-6			
Concentration	>= 0,0015	<	0,01	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 3		H301	
	Acute Tox. 2		H330	Route of exposure: Inhalation exposure
	Skin Corr. 1B		H314	
	Aquatic Acute 1		H400	
	Aquatic Chronic 1		H410	
	Skin Sens. 1A		H317	
	Acute Tox. 3		H311	
	Eye Dam. 1		H318	

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400	M = 10
Skin Sens. 1A	H317	>= 0,0015 %

4. First aid measures**4.1. Description of first aid measures****General information**

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

After inhalation

When spray fog inhaled, seek medical aid.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 10 Flammable liquids

Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

8. Exposure controls/personal protection

8.1. Control parameters

Other information

-

8.2. Exposure controls

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness >= 0,5 mm

Breakthrough time >= 120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	liquid		
Colour	black		
Odour	characteristic		
Odour threshold			
Remarks	not determined		
pH value			
Value	8		
Concentration/H ₂ O	100		
Melting point			
Remarks	not determined		
Freezing point			
Remarks	not determined		
Initial boiling point and boiling range			
Remarks	not determined		
Flash point			
Value	> 60		°C
Flammability (solid, gas)			
not determined			
Upper/lower flammability or explosive limits			
Remarks	not determined		
Vapour pressure			
Remarks	not determined		
Vapour density			
Remarks	not determined		
Density			
Value	appr. 1,029		kg/l
Temperature	20	°C	
Solubility in water			
Remarks	not determined		
Solubility(ies)			

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

Remarks not determined

Partition coefficient: n-octanol/water

Remarks not determined

Ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

Viscosity

Remarks not determined

Efflux time

Value	26	to	40	s
Temperature	20	°C		
Method	DIN 53211 - 6 mm			

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

9.2. Other information**Non-volatile content**

Value	38,4	%
Method	calculated value	

10. Stability and reactivity**10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition productsCarbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.**11. Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)**2-methyl-2H-isothiazol-3-one**

Species rat
 LD50 120 mg/kg
 Method EPA
 Source 1 (reliable without restriction)

1,2-benzisothiazol-3(2H)-one

Species rat
 LD50 1193 mg/kg

Acute dermal toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)**2-methyl-2H-isothiazol-3-one**

Species rat
 LD50 242 mg/kg
 Source 1 (reliable without restriction)

Acute inhalational toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)**2-methyl-2H-isothiazol-3-one**

Species rat
 LC50 0,1 mg/l
 Duration of exposure 4 h
 Administration/Form Dust/Mist
 Source 1 (reliable without restriction)

Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)**2-methyl-2H-isothiazol-3-one**

evaluation Causes burns.

1,2-benzisothiazol-3(2H)-one

evaluation Irritating to skin.

Serious eye damage/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation (Components)**2-methyl-2H-isothiazol-3-one**

evaluation Causes severe caustic burns to skin and eyes.

1,2-benzisothiazol-3(2H)-one

evaluation Irritating to eyes.

Sensitization

evaluation May cause sensitization by skin contact.

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks The classification criteria are met.

Sensitization (Components)**2-methyl-2H-isothiazol-3-one**

evaluation May cause sensitization by skin contact.

1,2-benzisothiazol-3(2H)-one

Reference substance 1,2-benzisothiazol-3(2H)-one
 evaluation May cause sensitization by skin contact.

Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)**Single exposure**

Method Calculation method (Regulation (EC) No. 1272/2008)
 Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Other information

No toxicological data are available.

12. Ecological information**12.1. Toxicity****General information**

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)**1,2-benzisothiazol-3(2H)-one**

Species Oncorhynchus mykiss (rainbow trout)
 LC50 2,18 mg/l
 Duration of exposure 96 h

Daphnia toxicity (Components)**2-methyl-2H-isothiazol-3-one**

Species Daphnia magna (Water flea)
 NOEC 0,044 mg/l
 Duration of exposure 21 d

1,2-benzisothiazol-3(2H)-one

Species Daphnia magna (Water flea)
 EC50 2,94 mg/l

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

Duration of exposure 48 h

Algae toxicity (Components)**2-methyl-2H-isothiazol-3-one**

EC50 0,157 mg/l

Duration of exposure 96 h

12.2. Persistence and degradability**General information**

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)**2-methyl-2H-isothiazol-3-one**

evaluation Readily biodegradable.

1,2-benzisothiazol-3(2H)-one

evaluation Readily biodegradable.

12.3. Bioaccumulative potential**General information**

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient: n-octanol/water

Remarks not determined

12.4. Mobility in soil**General information**

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment**General information**

For this subsection there is no ecotoxicological data available on the product as such.

12.6. Other adverse effects**General information**

For this subsection there is no ecotoxicological data available on the product as such.

13. Disposal considerations**13.1. Waste treatment methods****Disposal recommendations for the product**Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.**Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

14. Transport information

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

15. Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC ***

VOC (EU) 1,1 % 11 g/l

16. Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A

Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG - International Maritime Code for Dangerous Goods
 IATA - International Air Transport Association
 IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS - Globally Harmonized System of Classification and Labelling of Chemicals

Trade name: Hesse COOL-COLOR, silk matt HB 65285-9005

Version: 23 / WORLD

Revision: 12.01.2021

Replaces Version: 22 / WORLD

Print date: 18.10.21

EINECS - European Inventory of Existing Commercial Chemical Substances
CAS - Chemical Abstracts Service (division of the American Chemical Society)
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL - Lowest Observed Adverse Effect Level
LOEL - Lowest Observed Effect Level
NOAEL - No Observed Adverse Effect Level
NOEC - No Observed Effect Concentration
NOEL - No Observed Effect Level
OECD - Organisation for Economic Cooperation and Development
VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.