

### >Product description

The gloss level of coloured lacquers can be increased using the gloss resin solution. Mix at a ratio of 9 : 1 coloured lacquer to gloss resin solution to change a semi matt lacquer to a satin gloss lacquer. This is possible with the following coloured lacquer series: DB 45205-(colour tone); DB 45245-(colour tone)

### >Areas of application

#### >Surface Preparation

#### >Finishing

### >Application

Application
Spraying
other spraying methods

### >Technical data

Flow time (+/- 15 %)	36 s / DIN 53211 - 6 mm
Appearance	not relevant
Density series kg/l	0.98
Form of delivery	fluid
Non-volatile content series %	43
VOC EU %	58 %
VOC FR	C
Shelf life in weeks	52

### >Ordering information

Order number	Gloss level 60° (Gloss)	Container Size
EL 460-0028	-	1 l, 5 l

### >Particular instructions

### >General information

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at [www.hesse-lignal.de](http://www.hesse-lignal.de) or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.