

>Product description

Simply mix your own matt colour lacquer. Add 10 % Matting concentrate EL 459-0099 in relation to the base lacquer for the following silk matt Colour lacquer ranges: DB 45245-(colour tone), DB 45205-(colour tone), DB 48885-(colour tone).

>Areas of application

>Surface Preparation

>Finishing

>Application

| |
|------------------------|
| Application |
| Spraying |
| other spraying methods |

>Technical data

| | |
|---|-------------------------|
| Proportion of renewable raw materials % | 0.4 |
| Flow time (+/- 15 %) | 62 s / DIN 53211 - 6 mm |
| Appearance | not relevant |
| Density series kg/l | 0.992 |
| Form of delivery | fluid |
| Non-volatile content series % | 31 |
| VOC EU % | 69 % |
| VOC FR | C |
| Shelf life in weeks | 52 |

>Ordering information

| Order number | Gloss level 60° (Gloss) | Container Size |
|--------------|-------------------------|----------------|
| EL 459-0099 | - | 1 l, 5 l |

>Particular instructions

>General information

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.hesse-lignal.de or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.