



>Product description

Adding Hesse PU Ring-proof additive EL 460-0046 increases the resistance against metal marking. To achieve this, the DB 45245-(colour tone) colour lacquer has the additive stirred into it at a ratio of 8.5 : 1.5.

>Areas of application

>Surface Preparation

>Finishing

>Application

Application
Spraying
other spraying methods

>Technical data

Proportion of renewable raw materials %	0.2
Flow time (+/- 15 %)	28 s / DIN 53211 - 4 mm
Appearance	not relevant
Density series kg/l	0.95
Form of delivery	fluid
Non-volatile content series %	35
VOC EU %	65 %
VOC FR	C
Shelf life in weeks	52

>Ordering information

Order number	Gloss level 60° (Gloss)	Container Size
EL 460-0046	-	1 l, 5 l

>Particular instructions

>General information

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.hesse-lignal.de or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.