

### >Product description

Fine structured additive to create structured lacquers. Easy to create by mixing Hesse UNA-COLOR DB 45245- (colour tone) with a textural additive at a ratio of 9 : 1.

### >Areas of application

#### >Surface Preparation

#### >Finishing

### >Application

Application
Spraying
other spraying methods

### >Technical data

Flow time (+/- 15 %)	not applicable keine Angabe
Appearance	not relevant
Density series kg/l	0.878
Form of delivery	Paste
Non-volatile content series %	35
VOC EU %	65 %
VOC FR	C
Shelf life in weeks	26

### >Ordering information

Order number	Gloss level 60° (Gloss)	Container Size
EL 460-0045	-	5 l

### >Particular instructions

### >General information

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at [www.hesse-lignal.de](http://www.hesse-lignal.de) or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.